

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
7 December 2000 (07.12.2000)

PCT

(10) International Publication Number  
WO 00/73746 A1

(51) International Patent Classification: G01F 23/26

(74) Agent: VAN BREDA, Jacques; Octroobureau Los en  
Stigter B.V., Weteringschans 96, NL-1017 XS Amsterdam  
(NL).

(21) International Application Number: PCT/NL00/00371

(22) International Filing Date: 30 May 2000 (30.05.2000)

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, US, UZ, VN, YU, ZA, ZW.


(25) Filing Language: Dutch

(26) Publication Language: English

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).(30) Priority Data:  
1012197 31 May 1999 (31.05.1999) NLPublished:  
— With international search report.(71) Applicant (for all designated States except US): TECH-  
NISCHE UNIVERSITEIT DELFT [NL/NL]; Ju-  
lianalaan 134, NL-2628 BL Delft (NL).For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR MEASURING A SMALL QUANTITY OF A LIQUID

WO 00/73746 A1



(57) Abstract: An apparatus for measuring a small quantity of a liquid, for example, in connection with a medical diagnostic test, comprising at least one chamber for receiving the liquid, which chamber comprises a bottom and upright side walls and at least two electrodes to connect to a voltage source and a measuring system for determining the electrical impedance between the electrodes. The electrodes are substantially incorporated in the bottom of the chamber, allowing the electrical impedance of the liquid itself to be determined.